SCS Global Services does hereby certify that an independent assessment has been conducted on behalf of:

Amorim Cork Composites

26112 110th Street, Trevor, WI, United States

For the following product(s):

See Addendum

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

FloorScore®

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m^3 (in compliance with CDPH/EHLB Standard Method v1.2-2017)





Registration # SCS-FS-03528

Valid from: June 1, 2019 to May 31, 2020

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.



Stanley Mather Kam

Stanley Mathuram, PE, Vice President SCS Global Services 2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA

Certification Addendum

Amorim Cork Composites

Certification: Registration # SCS-FS-03528 | Valid from: June 1, 2019 to May 31, 2020

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification;

certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.

Addendum FloorScore®

Conformance: Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom

and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³ (in compliance with

Products: Underlayment:

AcousticCork Quiet Comfort Plus Vapor Barrier Roll, AcoustiCORK PR60 6x4 MM Wave Textured Roll, AcoustiCORK Quiet Comfort, AcoustiCORK R25 2.5MM Thick Roll, AcoustiCORK R60 6MM Thick Roll, AcoustiCORK S130 13MM Thick Sheet, CorkPlus 250 Cork/EVA Underlayment for Resilient Flooring, LVT Total Comfort, PURC 200 Underlayment for Floating Resilient Flooring, RCLT 500/1000, Stress Cork R12 Crack

Suppression Membrane, T-51 Cork/Rubber, ECOx2 Underlayment

